

SERIES PETROL GENERATOR

For durable & long running operation with stable output voltage.

TOKAI®

M a d e T o L a s t



Model : TK950i



Model : EC1200CXi



Model : EC2500CXi



Model : EC3800CXi



Model : EC6500CXi / EC6500CXi-E



Model : EC8000CXi-E



Model : EC13000CXi-E

Technical Parameters

Model	TK950i	EC1200CXi	EC2500CXi	EC3800CXi	EC6500CXi / EC6500CXi-E	EC8000CXi-E	EC13000CXi-E	
Engine Type	2 stroke	Single Cylinder, 4 Stroke, Forced Air Cooling						
Displacement	63 cc	97 cc	195 cc	212 cc	389 cc	420 cc	622 cc	
Fuel Tank Capacity	4L	1.6L	18L		25L		48L	
Continuing Time	5.5H	-	15H		9H	8H	-	
Rated Voltage	240V / 50Hz						415V / 50Hz	
Voltage Regulator System	Automatic Voltage Regulation							
Rated Output	650W	-	2000W	2800W	5000W	6000W	9000W	
Max Output	800W	-	2200W	3100W	5500W	7000W	10000W	
Charging Voltage	12V (DC)							
Starting System	Easy Recoil Starter					Easy Recoil Starter / Electric Start		
Noise	64dB (A)	-	≤ 76dB (A)					
Outlets	1x13A	-	2x13A		2x13A,1x15A	3x13A,1x15A	2x13A,1x15A	-
Net Weight	17kg	20kg	43kg	54kg	77kg		86kg	143kg
Dimension	360 x 300 x 300 mm	420 x 295 x 370 mm	590 x 430 x 480 mm		675 x 540 x 540 mm		680 x 540 x 540 mm	850 x 620 x 650 mm
Stoke Code	880305016A	880305041	880305041	880305009	880305008	880305010	880305035	880305040